# US PHRF of South East Florida, Inc. 2014 Rating Application

SEND TO: US PHRF SE Florida, Inc. Fax: 954 276 5386
P.O. Box 820003 Email: rhorn@mhs.net
Pembroke Pines, FL 33082-0003 Web Site: www.phrfsef.com

OWNER INFORMATION

Name: Contact Phone #:

Name:	Contact Phone #:	
Address:	Email Address:	
City, State: Zip:	US Sailing Member: Yes / No #:	
Yacht Club:		

BOAT INFORMATION \* Please Provide all measurements in Feet decimal notation. Sail #: Boat Name: Boat Model/Type: Year Built: Mast/Boom Material: Alum / Carbon Fiber Manufacturer: Other Designer: Displacement Lbs: LOA: Ballast Lbs: LWL: Keel Type: Fin / Full / Wing / Shoal Draft Beam: Motor Type: Inboard / Outboard / Saildrive Draft: Prop Type: Folding/Feathering / Fixed

RIG INFORMATION * F	Please Provide all me	easurements in Feet p	er decimal notation	
Rig: Fractional / Ma	asthead (Circle one)			
I:	J:	ISP:	SPL/Jc:	SMW/SMG:
P:	PY:	E:	EY:	

To reference the US PHRF SEF Rules visit the following link http://www.phrfsef.com

### Section 1. HEADSAILS

Record the largest headsail you are declaring:	%	
Record the LP of the Largest Headsail you will declare:	ft.	
- Reference figure 1	sailing rules-	

## **Roller furling Credits**

HEADSAIL CREDITS: If you race with one or more Roller Furling headsail(s) any of the three credit variations must meet ALL of the Criteria. Only one credit will apply with the exception to where the owner added or removed the Roller Furler hardware or any portion of the hardware which was standard/stock equipment defined by the manufacture or Class rules.

Please take the time to read the following options and only select the one option if applicable that applies to you.

#### ROLLER FURLER Hardware Credit (+/- 2 sec/mi)

I elect to take the following credit and will conform to the following rules noted below.

Roller Furler hardware which has been added by owner and otherwise not define in the class rules or Yacht designer's specifications. Additionally the furler hardware must not be part of the base configuration of the boat to which the US PHRF base rating was derived. Meaning that the base rating assumes the hardware to be in place and defined by the Yacht specifications or vessels Class rules.

- ALL hardware including Drum and Swivel must be in place while racing.
- No restriction on use.

Check which applies.

☐ The roller furler drum and foil are NOT standard equipment supplied by the factory, specified by yacht designer or class rules and was added by myself or a previous owner per a modification to the vessel.
☐ I removed the roller furler or any portion which is part of the standard equipment supplied from the factory, specified by yacht designer or specified by class rules.

#### ROLLER FURLER Credit (+ 4 sec/mi)

I elect to take the following credit and will conform to the following rules noted below.

If you race with a roller furling headsail that meets <u>all\_of the "ROLLER FURLING HEADSAIL CREDIT" criteria.</u> (MUST MEET <u>ALL\_CRITERIA Defined below):</u>

- Use of Roller Furling required. Sail must be capable of being furled during racing.
  - Tack must be attached to drum.
  - Head must be attached to Head swivel.
  - Must be furled during racing except when changing headsails
- No restrictions on number or type of sails.
- No restriction on Sail Materials used
- Luff Length must be at least 2.5% shorter than the max headstay length (Headstay length is measured from deck sheer line to mast))

Definition of Heavy weather and Storm Jib:

- Sail must conform to the most current ISAF Offshore Regulations for Race Category 2 Monohull. Reference section 4.26.4 of the ISAF Offshore Regulations. Current ISAF regulations supersede the definitions noted below for reference.
  - storm jib of area not greater than 5% height of the foretriangle squared, with luff maximum length 65% height of the foretriangle;
  - a heavy-weather jib (or heavy-weather sail in a yacht with no forestay) of area not greater than 13.5% height
    of the foretriangle squared and without reef points;
  - Storm and heavy weather jib areas shall be calculated as: (0.255 x luff length x (luff perpendicular + 2 x half width))\* To apply to sails made in January 2012 and after.
- Exceptions to the Drum and Swivel attachment points during use of:
  - o While using a Storm Jib or Heavy-Weather Jib

#### ROLLER FURLER Cruising Headsail Credit (+9 sec/mi)

I elect to take the following credit and will conform to the following rules noted below. Select only one of the two configurations below.

If you race with a roller furling headsail that meets <u>all</u> of the "ROLLER FURLING HEADSAIL CREDIT" criteria. (MUST MEET ALL CRITERIA Defined below):

- This is the ONLY headsail declared during the racing year which is greater than 110% LP. No other headsail other than the declared Genoa used to acquire this Cruising Roller furler credit can be used during the course of the rated year.
  - 1. EXCEPTIONS

- 1. Except while using a Heavy weather Jib and Storm Jib. See definition of Heavy Weather Jib and Storm Jib defined below.
- 2. Except for using a Staysail.
  - 1. Staysail must not exceed the rated %LP
  - 2. Staysail's maximum sail area must not exceed 66% of the total foretriangle area
- Replacement sails purchased during the rated year <u>MUST</u> be of the same size, material
  and weight. All other exceptions must be reported to US PHRF SEF for review.
- Use of Roller Furling is required. Sail must be capable of being furled while racing.
  - 1. Tack must be attached to Drum.
  - 2. Head must be attached to Head swivel
- Luff Length must be at least <u>2.5%</u> shorter than the headstay length (Headstay length is measured from deck sheer line to mast))
- Has a Sunbrella material leech and foot cover attached to the sail sufficient to completely cover the sail when furled. Material must be stitched in place.
- All head sails must be of a woven polyester material (no exotic sail materials such as pentax, Mylar, Kevlar, spectra, technora, etc.)

Definition of Heavy weather and Storm Jib:

- Sail must conform to the most current ISAF Offshore Regulations for Race Category 2 Monohull. Reference section 4.26.4 of the ISAF Offshore Regulations. Current ISAF regulations supersede the definitions noted below for reference.
  - storm jib of area not greater than 5% height of the foretriangle squared, with luff maximum length 65% height of the foretriangle;
  - a heavy-weather jib (or heavy-weather sail in a yacht with no forestay) of area not greater than 13.5% height
    of the foretriangle squared and without reef points;
  - Storm and heavy weather jib areas shall be calculated as: (0.255 x luff length x (luff perpendicular + 2 x half width))\* To apply to sails made in January 2012 and after.
- Exceptions to the Drum and Swivel attachment points during use of:
  - While using a Storm Jib or Heavy-Weather Jib

Refe mea	2. MAINSA erence figure 2 of asurements. lainsail exceed any	the PHRF-SEF r	•				No
·	Check box if the Cook Class Rules or	lass rules or Yach Yacht designer s	• .			th Measur	rements
lf y	MGU (3/4 leed	iil) < 0.04*E h) = 0.22*E :h) = 0.38*E :h) = 0.65*E	vide the followi if greater if greater if greater if greater if greater	ing measuremen Record actual V Record actual V Record actual V Record actual V	/alue: /alue: /alue: /alue:		
☐ I have	a Hollow Lea	ch Mainsails	without ba	attens with	ROLLER FU	RLER Ge	ar
Myla • Rep	ls must be of a ar, Kevlar, spec lacement sails p weight. All ot	ctra, technora, ourchased durin	etc.) g the rated y	ear <u>MUST</u> be of	the same si	lze, mate	

☐ I have a Vertical or Air Batten Mainsail with ROLLER FURLER gear

Check this box if your mainsail rolls up inside the boom and is NOT standard equipment for your yacht type or has been added by you or a previous owner.

\*Max mainsail girth restrictions still apply.

Hardware is NOT standard equipment supplied by the factory and was added by myself or a previous owner per a modification to the vessel.
Section 3. SPINNAKERS
List the Largest Spinnaker type you will be using Symmetric / Asymmetric Check box if you will be using a Flasher (Cruising Spinnaker) during the racing year. SMW/SMG (Mid girth) not to exceed 165%. Note: Must not be flown on a spinnaker pole and must be tacked to the centerline of the boat.
Check box if your spinnaker pole "SPL" or Jc is oversized. SPL/Jc = ft. * Check the box only if the SPL or JC is oversized and NOT define in the class rules or Yacht designer's specifications.
Check box if your spinnaker is oversized. Increased SA = Sq. ft.
Section 4. PROPULSION  Check one that applies:  Yes OUTBOARD  Yes INBOARD
List out any propeller modifications from the stock production vessel. Include factory options or upgrades from the base vessel. (i.e. The stock production model comes with a fixed 2 Bladed solid prop and I purchased a 3 blade feathering prop as an option)
Section 5. MODIFICATIONS/STOCK BOAT  List out all Modification:
Section 6. ODR REGULATIONS  One Design Class- Does your yacht have an ODR class association?  Yes No N/A  If you answered "Yes" will you be racing under the accordance of the rules governed by the
class?   Yes No
If you answered "NO" List out any variances from the class rules.
Notation:
Section 7 CRUISING ACCOMPATIONS

### Section 7. CRUISING ACCOMIDATIONS

List out the cruising accommodations you would like considered for credit. Define the reasoning behind your request. Provide documentation supporting the request.

These are amenities added to the base boat which are NOT standard or included in the stock configuration of your Yacht for which the base rating was derived and defined for your vessel

Please remit with a copy of your local area PHRF certificate (if applicable) and a copy of

your USSA membership card.